

Technical drawing of a cabinet side profile. The drawing includes the following dimensions and labels:

- Overall height: 650 ± 2
- Top reinforcement material label: 裏補強材(t15)
- Right side height dimension: 190
- Front panel label: 前栈木
- Bottom panel thickness: 29
- Bottom panel height: 35
- Bottom panel width: 6
- Bottom panel offset: 19
- Bottom panel offset: 15
- Bottom panel width: 254

Technical drawing showing the installation details of a sink, including dimensions and material specifications.

Dimensions:

- Overall width: 650^{+2}_{-0}
- Counter opening width: 525
- Sink maximum width: 555^{+1}_{-3}
- Left side dimensions: 60, 45, 6, 31, 8
- Right side dimensions: 65, 50
- Water stop hole position: 110
- Bottom dimensions: 19, 15, 35, 7, 38, 40, 15

Labels and Materials:

- ポリウレタン樹脂充填 (Polyurethane resin filling)
- 裏補強材(t15) (Reinforcement material t15)
- 専用接着剤 (Special adhesive)
- 水栓穴位置 (Water stop hole position)
- 前栈木 (Front batten)
- 取付金具(SUZ t1.6) (Mounting bracket SUZ t1.6)
- M4x6 ナベ頭小ネジ (M4x6 Pan head screw)
- 裏補強材(t15) (Reinforcement material t15)
- 取付金具(SUZ t1.6) (Mounting bracket SUZ t1.6)
- M4x6 ナベ頭小ネジ (M4x6 Pan head screw)

810⁺¹₋₃

ポリウレタン樹脂充填

専用接着剤

21

15 6

7

合板 t15

M4 平ワッシャー
ユニクローム

M4x18 トラス頭タッピングネジ
ユニクローム

取付金具 (SU-21 t2.3)

20 7

864

製品名 HS810型アンダー樹脂シンク取付標準図 (YXカウンター Rタイプ)	尺 度	1/2 1/10
---	--------	----------

吉本産業株式会社